





THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL AND THE PROPERTY OF SOLBERG MANUFACTURING INC. AND IT IS FURNISHED TO YOU WITH THE EXPRESS UNDERSTANDING THAT IT WILL NOT BE REPRODUCED, COPIED IN ANY MANNER, LOANED OR OTHERWISE TRANSFERRED TO OTHERS ENTIRELY OR IN PART, NOR USED FOR ANY PURPOSE OTHER THAN FOR WHICH IT WAS FURNISHED. IT WILL BE RETURNED UPON REQUEST TO SOLBERG MANUFACTURING INC. THE ABOVE RESTRICTION IS IN ADDITION TO, AND DOES NOT IN ANY WAY ALTER, ANY OTHER RESTRICTIONS WHICH MAY APPLY TO THE INFORMATION CONTAINED HEREIN.

TOLERANCES

DIMENSIONS ARE FOR REFERENCE ONLY. ALL DIMENSIONS ARE SUBJECT TO CHANG UPON PRODUCTION.

UNLESS OTHERWISE SPECIFIED: -DIMENSIONS ARE IN INCHES -REF: APPROXIMATE DIMENSIONS, NO TOLERANCES AF -FINISH: BREAK EDGES TO .005-.020 RADIUS/CHAMFER



			ELEMENT SPECS					
			PART NUMBER		344	4P		
		MATERIAL		Paper				
/PN10 OUTLET FLANGE			FLOW RATE	1100 CFM		1869 m³/hr		
			SURFACE AREA		57.0 ft ²	5.3 m ²		
			I.D.		6.00"	152mm		
			O.D.	9.75"		248mm		
		HEIGHT	14.50"		368mm			
	MODEL #: CSL-344P-DN125	MATI	ERIAL: CARBON STEEL		FINISH: BLACK POWDER			
	MODEL NUMBER: CSL-344P-DN125						SHEET:	
							1 OF 1	
GE	DESCRIPTION: CSL-344P-DN125, BLACK							
S APPLY ER	PROJECT:	DRA	WN BY: DDH		APPROVED BY:	JEB		REV:
		DAT	FE: 9/19/2019		DATE: 9/19/2019			