









ELEMENT SPECS				
PART NUMBER	345P			
MATERIAL	Polyester			
FLOW RATE	1100 CFM	1869 m³/hr		
SURFACE AREA	22.1 ft ²	2.1 m ²		
I.D.	6.00"	152mm		
O.D.	9.75"	248mm		
HEIGHT	14.50"	368mm		

SOLBERG® Filtration • Separation • Silencing 630.773.1363 • www.solbergmfg.com

THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL AND THE PROPERTY OF SOLBERG MANUFACTURING INC.
AND IT IS FURNISHED TO YOU WITH THE EXPRESS
UNDERSTANDING THAT IT WILL NOT BE REPRODUCED, COPIED IN ANY MANNER, LOANED OR OTHERWISE TRANSFERRED TO OTHERS ENTIRELY OR IN PART, NOR USED FOR ANY PURPOSE OTHER THAN FOR WHICH IT WAS FURNISHED. IT WILL BE RETURNED UPON REQUEST TO SOLBERG MANUFACTURING INC. THE ABOVE RESTRICTION IS IN ADDITION TO, AND DOES NOT IN ANY WAY ALTER, ANY OTHER RESTRICTIONS WHICH MAY APPLY TO THE INFORMATION CONTAINED HEREIN.

TOLERANCES

DIMENSIONS ARE FOR REFERENCE ONLY. ALL DIMENSIONS ARE SUBJECT TO CHANGE **UPON PRODUCTION.**

UNLESS OTHERWISE SPECIFIED:
-DIMENSIONS ARE IN INCHES
-REF: APPROXIMATE DIMENSIONS, NO TOLERANCES APPLY
-FINISH: BREAK EDGES TO .005-.020 RADIUS/CHAMFER

MODEL #: CSL-345P-DN125	MATERIAL: CARBON STEEL	FINISH: BLACK POWDER	
MODEL NUMBER: CSL-345P-DN12	5		SHEET:

DESCRIPTION: CSL-345P-DN125 FINAL ASSEMBLY

PROJECT:	DRAWN BY: CRW	APPROVED BY:	RE\
SD14649	DATE : 6/6/2003	DATE:	В