







	ELEMENT SPECS		
PART NUMBER	231P		
MATERIAL	Polyester		
FLOW RATE	300 CFM	510 m³/hr	
SURFACE AREA	4.5 ft ²	0.4 m ²	
I.D.	SEE DRAWING		
O.D.	SEE DRAWING SEE DRAWING		
HEIGHT			



THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL AND THE PROPERTY OF SOLBERG MANUFACTURING INC. AND IT IS FURNISHED TO YOU WITH THE EXPRESS UNDERSTANDING THAT IT WILL NOT BE REPRODUCED, COPIED IN ANY MANNER, LOANED OR OTHERWISE TRANSFERRED TO OTHERS ENTIRELY OR IN PART, NOR USED FOR ANY PURPOSE OTHER THAN FOR WHICH IT WAS FURNISHED. IT WILL BE RETURNED UPON REQUEST TO SOLBERG MANUFACTURING INC. THE ABOVE RESTRICTION IS IN ADDITION TO, AND DOES NOT IN ANY WAY ALTER, ANY OTHER RESTRICTIONS WHICH MAY APPLY TO THE INFORMATION CONTAINED HEREIN.

TOLERANCES

DIMENSIONS ARE FOR REFERENCE ONLY. ALL DIMENSIONS ARE SUBJECT TO CHANGE **UPON PRODUCTION.**

UNLESS OTHERWISE SPECIFIED:
-DIMENSIONS ARE IN INCHES
-REF: APPROXIMATE DIMENSIONS, NO TOLERANCES APPLY
-FINISH: BREAK EDGES TO .005-.020 RADIUS/CHAMFER

	MODEL NUMBER: 231P	SHEET:
WIODEL NOWIBER. 231P		1 OF 1

DESCRIPTION: 231P, POLY

PROJECT:	DRAWN BY: CRW	APPROVED BY: M.C.	REV
SD21099	DATE : 7/28/2011	DATE : 7/28/2011	Α